





You have a job to do and chances are, there's a 4900 that can help you do it.

In fact, it would be hard to find a truck as powerful and versatile. Fortunately, you have all the options available to help you spec the right truck for your demanding jobs. Of course, this is just the beginning. If there's something you need, just ask.









CAB TYPE

Standard galvannealed steel with roped-in windshield

Severe Duty galvannealed steel with bonded windshield

HOOD TYPE

Fiberglass traditional non-sloping hood (SF, SB, EX)

Supervisibility fiberglass hood (SB)

Three-piece butterfly hood (XD)

ENGINE

Detroit™ DD13®, 12.8L, 350-470HP, 1250-1650Ib-ft.

Detroit[™] DD15[®] TC, 14.8L, 455-505HP, 1550-1750lb-ft.

Detroit[™] DD16[®], 15.6L, 475-600HP, 1850-2050lb-ft.

Detroit™ Series 60® Tier III, 14L, 425-500HP, 1475-1550lb-ft.

Cummins ISX15, 15.0L, 400-600HP, 1450-2050lb-ft.

TRANSMISSION

Eaton Fuller FR-13210B (7, 10, 11, 13, 15 and 18-speed)

Eaton Fuller UltraShift PLUS

Allison Automatic 4000, 4500, 4700

FRONT AXLE

Detroit™ single 12,000-20,000 lbs

Hendrickson single 12,500 lbs

Meritor single 12,000-23,000 lbs

Meritor tandem @ 40,000 lbs (available with Set Back Axle only)

REAR AXLE

Detroit tandem 40,000-46,000 lbs

Meritor single 23,000 lbs

Meritor tandem 40,000-70,000 lbs

Meritor tridem 69,000-77,000 lbs

Sisu tandem 70,000 lbs

Sisu tridem 105,600 lbs

FRONT SUSPENSION

Taperleaf 12,000-20,000 lbs

Flatleaf 14,600-23,000 lbs

REAR SUSPENSION

AirLiner® 23,000-69,000 lbs

Hendrickson 40,000-65,000 lbs

Chalmers 46,000-52,000 lbs

Neway 46,000-78,000 lbs

Reyco 23,000 lbs

TufTrac[™] 40,000-52,000 lbs

BRAKES

WABCO 4S/4M and 6S/6M Anti-lock Braking System (ABS) with and without traction enhancement

SAFETY

Roll stability control

FRAME

Single-channel @ 2.5 million RBM

Double-channel @ 3.2 million RBM and 4.5 million RBM

Triple-channel @ 5.6 million RBM

Partial frame liners available for increased RBM in specific areas. See dealer for details.

FUEL TANK

Aluminum 25" cylindrical 60-150 gallon (227-567 liter) RH or LH

Aluminum 23" cylindrical 50-150 gallon (189-567 liter) RH or LH

Combination fuel/hydraulic tanks available in various sizes

DEF TANK

6, 13, 23 gallon (23, 49, 87 liter)



For the Western Star Dealer nearest you, call 1-866-850-STAR | WESTERNSTAR.COM